

## Specification & Technical Data Sheet

## Part Number: RWC-182CS

## 18-02 OAS CMR - GRAY

|           | Conductor<br>AWG Size: | 18   |
|-----------|------------------------|--|
|           | Vive Size:             | 7 Strand Bare Copper                                     |
|           |                        |  |
| <b>2.</b> | Insulation             |  |
| (         | 🖗 Material:            | PVC  |
| (         | Wall Thickness:        | 0.010"   |
| (         | Color Code:            | 1-Black; 2-Red   |
| 3.        | Assembly               |  |
| (         | Cable Lay Length:      | 3.00" LHL (4.00 Tw/Ft)                                   |
| (         | 🖗 Shield:              | Shielded   |
| (         | 🖗 Drain:               | 24awg 7 Strand Tinned Copper                             |
| (         | Ø Braid:               |  |
| 4         | Jacket                 |  |
| (         | 🛇 Material:            | PVC  |
| (         | Wall Thickness:        | 0.015"   |
| (         | Diameter:              | 0.165"   |
| (         | 🖗 Color:               | Gray   |
| (         | Q Ripcord:             | Yes  |
| (         | 🛇 Weight:              | 21.0000 lbs/Mft.   |
| 5. I      | Markings               |  |
| (         | V Type:                | Inkjet Printer   |
| (         | Legend:                | Sequential Foot Markers; UL Standard Legend; Riser Rated |
| (         | Footage Markers:       | Yes  |
| 5. I      | Electricals            |  |
| (         | Impedance:             | Ω/Mft.   |
| (         | Capacitance:           | 47 pF/ft +/- 10%   |
| (         | OC Resistance:         | 6.92 Ω/Mft. @ 20°C                                       |
| 7 (       | Standards              |  |
|           |                        |  |

## 7. Standards

- UL listed as type CL3R per UL standard 13 and as type FPLR 75°C per UL standard 1424
- All materials used in the manufacture of this cable are RoHS II & REACH compliant
- Maximum Operating Voltage: 300V RMS
- Made in the USA