

## Specification & Technical Data Sheet

Part Number: RWC-184F

## 18-04 SOLID BC NS FPLR - RED

1. Conductor

AWG Size: 18

Type: Solid Bare Copper

2. Insulation

Material: PVCWall Thickness: 0.010"

Color Code: 1-Black; 2-Red; 3-Brown; 4-Blue

3. Assembly

Cable Lay Length: 3.00" LHL (4.00 Tw/Ft)

Shield: NonDrain: N/A

Braid:

4. Jacket

Material: PVC
Wall Thickness: 0.020"
Diameter: 0.187"
Color: Red
Ripcord: Yes

Weight: 32.0000 lbs/Mft.

5. Markings

Type: Inkjet Printer

Legend: Sequential Foot Markers; UL Standard Legend; Riser Rated

Footage Markers: Yes

6. Electricals

 $\bigcirc$  Impedance: Ω/Mft.

Capacitance: 26 pF/ft +/- 10%DC Resistance: 6.39 Ω/Mft. @ 20°C

7. Standards

UL listed as type CL3R per UL standard 13 and as type FPLR 75°C per UL standard 1424

All materials used in the manufacture of this cable are RoHS II & REACH compliant

Maximum Operating Voltage: 300V RMS

Made in the USA

