

Specification & Technical Data Sheet

Part Number: RWC-P182PEPS

18-2P EACH PAIR SHIELDED CMP - NATURAL JACKET

1. Conductor

AWG Size: 18

Type: 7 Strand Bare Copper

2. Insulation

Material: PlenumWall Thickness: 0.007"

© Color Code: 1-Black/Red; 2-White/Green

3. Assembly

Cable Lay Length:

Shield: Individually Shielded

Orain: 24awg 7 Strand Tinned Copper

Braid:

4. Jacket

Material: Plenum
Wall Thickness: 0.015"
Diameter: 0.168"
Color: White
Ripcord: Yes

Weight: 33.0000 lbs/Mft.

5. Markings

Type: Inkjet Printer

Legend: Sequential Foot Markers; UL Standard Legend; Plenum Rated

Footage Markers: Yes

6. Electricals

Impedance: 39.0 Ω/Mft.
Capacitance: 46.8 pF/ft +/- 10%
DC Resistance: 6.92 Ω/Mft. @ 20°C

7. Standards

UL listed as type FPLP 75°C per UL standard 1424 or CL3P per UL Standard 13, CMP per UL 444

All materials used in the manufacture of this cable are RoHS II & REACH compliant

Maximum Operating Voltage: 300V RMS

Made in the USA