

Specification & Technical Data Sheet

Part Number: RWC-P222CS/M1-WH/GN

22-02 OAS CMP - NATURAL W/ GREEN STRIPE

1	Conductor	
	AWG Size:	22
	Victorial Contraction of the second s	7 Strand Bare Copper
	e Type.	
2.	Insulation	
	Ø Material:	Plenum
	Wall Thickness:	0.007"
	Color Code:	1-Black; 2-White
3.	Assembly	
	Cable Lay Length:	
	Shield:	Shielded
	Orain:	
	Ø Braid:	
4.	Jacket	
	Material:	Plenum
	Wall Thickness:	0.015"
	Oiameter:	0.120"
	Color:	White w/ Green Stripe
	Q Ripcord:	Yes
	🥥 Weight:	11.0000 lbs/Mft.
5.	Markings	
	V Type:	Inkjet Printer
	C Legend:	Sequential Foot Markers; UL Standard Legend; Plenum Rated
	Footage Markers:	Yes
6.	Electricals	
	Impedance:	Ω/Mft.
	Capacitance:	47 pF/ft +/- 10%
	DC Resistance:	17.50 Ω/Mft. @ 20°C

7. Standards

- UL listed as type FPLP 75°C per UL standard 1424 or CL3P per UL Standard 13, CMP per UL 444
- All materials used in the manufacture of this cable are RoHS II & REACH compliant
- Maximum Operating Voltage: 300V RMS
- Made in the USA